

US009924955B2

(12) United States Patent

Weekes et al.

(10) Patent No.: US 9,924,955 B2

(45) **Date of Patent:** Mar. 27, 2018

(54) ORTHOPAEDIC REAMER CONNECTOR

(71) Applicant: Symmetry Medical Manufacturing, Inc., Warsaw, IN (US)

(72) Inventors: Stuart Weekes, Oxford (GB); James

Truscott, Swindon (GB); Guillaume Kerboul, Crudwell (GB)

(73) Assignee: Symmetry Medical Manufacturing,

Inc., Warsaw, IN (US)

(*) Notice: Subject to any disclaimer, the term of this

patent is extended or adjusted under 35

U.S.C. 154(b) by 638 days.

(21) Appl. No.: 14/547,887

(22) Filed: Nov. 19, 2014

(65) Prior Publication Data

US 2016/0135818 A1 May 19, 2016

(51) Int. Cl.

A61B 17/16 (2006.01)

F16D 1/02 (2006.01)

A61B 17/17 (2006.01)

A61B 17/00 (2006.01)

(52) U.S. Cl.

CPC A61B 17/1666 (2013.01); A61B 17/1613 (2013.01); A61B 17/1617 (2013.01); A61B 17/1675 (2013.01); A61B 17/1684 (2013.01); A61B 17/1735 (2013.01); F16D 1/02 (2013.01); A61B 17/1778 (2016.11); A61B 2017/00464 (2013.01)

(58) Field of Classification Search

(56) References Cited

U.S. PATENT DOCUMENTS

| 5,658,290 | A | 8/1997 | Lechot |
|--------------|----|---------|----------------|
| 6,854,742 | B2 | 2/2005 | Salyer et al. |
| 7,115,119 | B2 | 10/2006 | Desarzens |
| 8,323,284 | B2 | 12/2012 | Ferreira |
| 8,366,713 | | 2/2013 | Long et al. |
| 8,398,642 | B2 | 3/2013 | Weekes |
| 8,439,920 | B2 | 5/2013 | Ryall et al. |
| 2003/0216716 | A1 | 11/2003 | Desarzens |
| 2012/0023733 | A1 | 2/2012 | Cannell et al. |
| 2013/0213678 | A1 | 8/2013 | Weekes |
| 2013/0253520 | A1 | 9/2013 | Ryall et al. |
| | | | |

FOREIGN PATENT DOCUMENTS

| WO | 03/094739 A | 12 | 11/2003 |
|----|-------------|------------|---------|
| WO | 2010/004267 | 4 1 | 1/2010 |

OTHER PUBLICATIONS

Extended European Search Report dated Apr. 21, 2016 for European Patent Application No. 15 19 1155 (6 pages).

Primary Examiner — Andrew Yang (74) Attorney, Agent, or Firm — Taylor IP, P.C.

(57) ABSTRACT

An orthopedic reamer connector includes a base shaped to allow for connection of an orthopedic reamer having a connection surface and being configured to rotatably connect to a rotary actuator; two pairs of holders associated with the connection surface that each have a first holder and a second holder that forms an acute angle relative to said first holder. The first holders are opposed to each other by about 180 degrees and the second holders are opposed to each other by about 180 degrees. A pair of stops are associated with each of the two pairs of holders. Each pair of stops has a first stop associated with the first holder and a second stop associated with the second holder.

18 Claims, 3 Drawing Sheets

